

X-TREME[®] MASTIC

1. PRODUCT IDENTIFICATION

Trade Names	X-TREME MASTIC
Chemical Name	Asphalt Emulsion
Synonyms	N/A
Hazardous Ingredients/OSHA	Chemical families: A. Bitumen/Asphalt B. Synthetic rubber C. Fatty acids D. Polymers
Hazard	No evidence of serious health hazards exists
Carcinogenic ingredients/ OSHA/NTP	Bitumen
IARC	None

2. WARNING STATEMENTS

Avoid prolonged or frequent skin contact, as the presence of emulsifying and de-emulsifying agents during application may irritate the skin.

3. PHYSICAL AND CHEMICAL DATA

Appearance	Brown to black
Specific Gravity	(H ₂ O = 1): 1.028 (S) 1.034 (R) 1.13 (T)
Solubility in Water	Insoluble
Percent Volatiles	None
Boiling Point	N/A
Vapor Pressure (mm Hg)	N/A
Vapor Density (Air = 1)	N/A
Evaporation Rate	N/A

4. FIRE PROTECTION

Bitumen emulsions are water based products and as such will not burn. In cases of fire in the vicinity of drums, cool with water.

5. REACTIVITY DATA

Contact with strong oxidizing agents may create gelling and water condensation.

6. HEALTH HAZARD DATA

Exposure Limits: Avoid prolonged or frequent skin contact.

7. PHYSIOLOGICAL EFFECTS SUMMARY

Acute: Skin irritation and rash

Chronic: Dermatitis

8. PRECAUTIONS FOR SAFE HANDLING

Avoid contact with eyes.

Avoid inhalation.

Avoid prolonged or frequent skin contact.

Avoid ingestion.

9. PROTECTION AND CONTROL MEASURES

Protective Equipment – Use of clothing, gloves, and/or barrier cream is recommended for skin protection.

Respiratory Protection – Inhalation should be avoided, but is not considered to be hazardous.

Ventilation – Use local exhaust ventilation when applying in an enclosed area.

10. EMERGENCY AND FIRST AID PROCEDURES

For ingestion – DO NOT induce vomiting. Keep at rest and get prompt medical attention.

For eye contamination – Irrigate eyes with water.

For skin contact – Wash affected areas of the body with proprietary hand cleaner, then wash with soap and water.

Contact physician as needed for any of the above occurrences.

11. SPILL AND DISPOSAL PROCEDURES

Contain spillages with sand or earth and remove by normal methods. Dispose of according to State and Local regulations. If the Bitumen enters a water course or sewer, advise respective water authority. The non-cured and cured material is non-toxic and non-flammable and can be disposed of in land fill sites.

OTHER PRECAUTIONS

For Additional Information Contact:

Office of Environmental Affairs

1-800-882-1896

Tex-Trude, LLP, P.O. Box 58, Channelview, TX 77530

LIMITED WARRANTY

Tex-Trude warrants this product to meet the published specifications and to be free of defects in workmanship and materials at the time of shipment from our factory. If any X-TREME material proves to contain manufacture defects that substantially affect the performance, then Tex-Trude will at their option replace the material or refund the purchase price. This limited warranty is the only warranty offered by Tex-Trude, LP as it relates to X-TREME products. There are no other warranties, including the implied warranties of merchantability or fitness for a particular purpose. Tex-Trude specifically disclaims liability for any incidental, consequential, or other damages.