

X-TREME® DOUBLE-SIDED TAPE

Tex-Trude X-TREME Double Sided Tape is a high strength, double-sided tape comprised of rubberized asphalt. The tape is supplied in rolls and utilizes both inner and outer release sheets that are removed prior to application. The X-TREME Double Sided Tape is designed to seal the X-TREME Vapor Barrier to concrete, cinder block and other masonry.

INSTALLATION ›

Prior to installation, perform a visual inspection that all dust, dirt, debris, has been removed from the X-TREME Vapor Barrier to achieve maximum adhesion. Apply the X-TREME Double Sided Tape by removing the outer release paper and press the tape firmly to surface, next; remove inner release liner, and firmly press the X-TREME Vapor Barrier onto the tape. For Crawl Spaces: use a term bar to secure.

Storage: Store out of direct sunlight.

Warm conditions: Perform normal installation, using industry knowledge of the guidelines for Vapor Barriers.

Cold conditions: For cold weather applications, we suggested to condition the tape in a warm environment 8 hours prior to use. This will help the tape reach its best performance.

TECHNICAL DATA >

DOUBLE-SIDED TAPE		PACKAGING	
Thickness	60 mil	Size	2"x 50'
Permeance	0.01	Color	Black
Application Temperature	30°F-120°F	Weight	4 lbs/ea
Recommended Storage Conditions	60°F-85°F		
VOC	No VOC's		

LIMITED WARRANTY >

Tex-Trude warrants this product to meet the published specifications and to be free of defects in workmanship and materials at the time of shipment from our factory. If any X-TREME material proves to contain manufacture defects that substantially affect the performance, then Tex-Trude will at their option replace the material or refund the purchase price. This limited warranty is the only warranty offered by Tex-Trude, LP as it relates to X-TREME products. There are no other warranties, including the implied warranties of merchantability or fitness for a particular purpose. Tex-Trude specifically disclaims liability for any incidental, consequential, or other damages.