

# X-TREME® GRIP BACK TAPE

---

Tex-Trude X-TREME Grip Back Tape is composed of a self-adhering high performance polymer asphalt adhesive with a composite backing that bonds to concrete with incredible strength. X-TREME Grip Back Tape is designed to seal the seams of the X-TREME Vapor Barrier and mechanically bond the concrete and X-TREME Vapor Barrier. It may also be used to repair penetrations coming through the slab and to make small repairs.

## INSTALLATION ›

---

Prior to installation, perform a visual inspection of the X-TREME Vapor Barrier to insure a 6" overlap has been achieved and all dust, dirt, debris and moisture has been removed from the X-TREME Vapor Barrier to achieve maximum adhesion. X-TREME Grip Back Tape may also be used in additional areas where support may be needed. These areas need to be determined by Architect, Engineer, or other personnel.

**Slab Penetration:** You can install the X-TREME Grip Back Tape on small openings around penetrations that consist of 1" or smaller. For larger openings around penetrations, cut out a minimum of 12" and one-half times the penetration circumference, using X-TREME Vapor Barrier. Cut slits in the boot half the width of the film. Slide the boot over the penetration. The boot is to be in flat and firm contact with the X-TREME Vapor Barrier. It is important to tape the boot and the penetration and around the base.

**Storage:** Store out of direct sunlight.

**Warm conditions:** Perform normal installation, using industry knowledge of the guidelines for Vapor Barriers.

**Cold conditions:** For cold weather applications, we suggested to condition the tape in a warm environment 8 hours prior to use. This will help the tape reach its best performance.

**Note:** Only use X-TREME Accessory Products including X-TREME Tapes, X-TREME Mastic and X-TREME SLM to seal seams, edges, and penetrations.

## TECHNICAL DATA ›

### X-TREME GRIP BACK TAPE

Thickness 66 mil

Peel Adhesion 70 lb f/in

Permeance 0.02

Cold Weather Resistance Excellent

### PACKAGING

Size 6"x 200'

Weight 14 lbs/ea

Rolls Per Case 2

Color Black

## LIMITED WARRANTY ›

Tex-Trude warrants this product to meet the published specifications and to be free of defects in workmanship and materials at the time of shipment from our factory. If any X-TREME material proves to contain manufacture defects that substantially affect the performance, then Tex-Trude will at their option replace the material or refund the purchase price. This limited warranty is the only warranty offered by Tex-Trude, LP as it relates to X-TREME products. There are no other warranties, including the implied warranties of merchantability or fitness for a particular purpose. Tex-Trude specifically disclaims liability for any incidental, consequential, or other damages.