

X-TREME® STAKES

Tex-Trude X-TREME Stakes are concrete form stakes designed to be left permanently in place for interior forming applications. X-TREME Stakes, used with X-TREME Vapor Barrier and X-TREME Mastic, are part of the X-TREME Forming System that meets the installation standards of ASTM E1643.

X-TREME Stakes are sealed directly to the X-TREME Vapor Barrier and is cut off above the seal but below the finished concrete surface. Each X-TREME Stake is Pre-pointed and has Pre-Drilled holes for duplex nails or self-tapping screws. Available in various lengths in 25 piece bundles.

INSTALLATION ›

Dip the pointed end in the X-TREME Mastic (1 Gallon of X-TREME Mastic per bundle recommended). Ensure you have a generous amount of X-TREME Mastic on the stake before driving the X-TREME Stake through the X-TREME Vapor Barrier. Once the X-TREME Stake is in place, perform a visual inspection and ensure the penetration is completely sealed. Apply additional X-TREME Mastic if needed to form a monolithic seal to the X-TREME Vapor Barrier. DO NOT Pull the stake out. Cut the stake off above the seal but below the concrete finished surface. The lower portion remains in place permanently sealing the penetration.

TECHNICAL DATA ›

Length	18"	24"	36"	48"
Diameter	7/8"	7/8"	7/8"	7/8"

LIMITED WARRANTY ›

Tex-Trude warrants this product to meet the published specifications and to be free of defects in workmanship and materials at the time of shipment from our factory. If any X-TREME material proves to contain manufacture defects that substantially affect the performance, then Tex-Trude will at their option replace the material or refund the purchase price. This limited warranty is the only warranty offered by Tex-Trude, LP as it relates to X-TREME products. There are no other warranties, including the implied warranties of merchantability or fitness for a particular purpose. Tex-Trude specifically disclaims liability for any incidental, consequential, or other damages.



For more than 20 years, X-TREME® Vapor Barriers from Tex-Trude have set the industry standards for durability, dependability and life-cycle superiority.

Chris Hirsekorn
X-TREME Vapor Barrier
Sales Leads

☎ 713.481.3430 / 832.594.4848
✉ chirsekorn@tex-trude.com

Amanda Solis
X-TREME Vapor Barrier
Customer Service

☎ 713.481.3415
✉ asolis@tex-trude.com

Amy McNair
X-TREME Vapor Barrier
Specifications

☎ 713.481.3442
✉ amcnair@tex-trude.com