

X-TREME[®] TAPE

Tex-Trude X-TREME Tape is composed of a 7.5 mil thick strong self-adhering rubber based adhesive that has a high tack for a secure bond and is designed to seal the seams of the X-TREME Vapor Barrier Systems. It is also used to seal penetrations coming through the slab, small repairs, and patch areas.

INSTALLATION ›

Prior to installation, preform a visual inspection of the X-TREME Vapor Barrier to insure a 6" overlap has been achieved and all dust, dirt, debris and moisture has been removed from the X-TREME Vapor Barrier to achieve maximum adhesion.

Slab Penetration: Using X-TREME Vapor Barrier material, cut out a minimum of 12" and one-half times the pipe circumference. Cut slits in the boot half the width of the film. Slide the boot over the penetration. The boot is to be in flat contact with the X-TREME Vapor Barrier. It is important to tape the boot to the pipe and around the base.



Warm conditions: Store out of direct sunlight. Perform normal installation, using industry knowledge of the guidelines for vapor barriers.

Cold conditions: In cold weather applications, it is suggested to condition the tape 8 hours in a warm environment prior to use. This will help the tape reach its optimal performance.

TECHNICAL DATA ›

X-TREME TAPE		PACKAGING	
Thickness	7.5 mil	Size	4"x 180'
Permeance	0.112	Rolls Per Case	12
Tensile Strength	25 lbs/in	Weight	4 lbs/ea
Elongation	85%	Weight Per Case	48 lbs
Adhesion	75 oz/in	Color	Red
Cold Weather Resistance	Excellent		
Application Temperature	30°F - 160°F		
Recommended Storage Conditions	60°F - 80°F		

LIMITED WARRANTY ›

Tex-Trude warrants this product to meet the published specifications and to be free of defects in workmanship and materials at the time of shipment from our factory. If any X-TREME material proves to contain manufacture defects that substantially affect the performance, then Tex-Trude will at their option replace the material or refund the purchase price. This limited warranty is the only warranty offered by Tex-Trude, LP as it relates to X-TREME products. There are no other warranties, including the implied warranties of merchantability or fitness for a particular purpose. Tex-Trude specifically disclaims liability for any incidental, consequential, or other damages.

Note: Only use X-TREME Accessory Products including X-TREME Tapes, X-TREME Mastic and X-TREME SLM to seal seams, edges, and penetrations.